

QuickSeam™ Corner Flashing

1. Description

The Firestone QuickSeam™ Corner Flashing is a 216 mm in diameter round piece of uncured EPDM FormFlash laminated to QuickSeam Tape. It is designed to flash outside corners or to be used as a cover patch where appropriate.



2. Preparation

The RubberCover™ EPDM surfaces and/or mating surfaces must be prepared with QuickPrime™ Plus, using a QuickScrubber™ tool. Use of other products is not allowed. Restore the product to room temperature prior to use if exposed to temperatures below 15°C for prolonged periods.

3. Application

On cold days with ambient temperature below 15°C, the use of a heat gun is recommended to warm the QuickSeam Corner Flashing and to ensure good formability.

Note: QuickSeam FormFlash is a non-vulcanized product and cures after installation. Correct use, accurate installation technique and installation according general roofing practice will result the final characteristics and proper functioning of the product.

4. Coverage

One piece per corner.

5. Characteristics

Technical	EPDM Flashing	QuickSeam Tape
• Base	EPDM	Rubber polymers
• Color	Black	Black
• Solvents	None	None
• Solids	100 %	100 %
• State	Uncured	Cured
• Thickness	1.6 mm	0.6 mm
• Diameter	216 mm	216 mm

6. Packaging/ Storage/ Shelf Life

Packaging	20 pieces per carton
Part number	W56RAC1646

Storage: Store in original unopened containers at temperatures between 15°C and 25°C, in a well-ventilated place. Keep the material dry and out of direct sunlight until ready for application.

Shelf Life: 12 months can be expected if stored in above-mentioned conditions. Verify production date on each carton packaging. Shelf life will be reduced if exposed to higher temperatures. Shelf life information is only a recommendation and not a fact of life. The real expiration date highly depends on the history of storage and handling of the accessories.

7. Precautions

Refer to Safety Data Sheet.

This document replaces any other document published previous. This sheet is meant to highlight Firestone product information based on latest knowledge and experience and is subject to change without notice (check the Firestone website for latest document version). Above mentioned values are based on tested samples and may vary within applicable tolerances. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. No Firestone representative is authorized to vary this disclaimer.